

직냉식 25,30,45 올스텐 정육숙성고 (아날로그)

Direct Cooling Meat Maturing Cabinets (Analog)



직냉식



아날로그



24 hour
신선냉장



올스텐



냉기순환팬

| 재질 | 올스텐 | 컨트롤러 | 아날로그

*정육숙성고 GRAND제품 별매



CWSR-630(2G)			
외부크기(mm)	W627×D800×H1900	선반(개)	3
내부크기(mm)	W527×D650×H1441	중량(kg)	95
내용적(L)	냉장전용 : 530	소비전력	270 W
온도범위	냉장 -10℃ ~ 10℃		

*장도어 가능



CWSR-830(1G)			
외부크기(mm)	W850×D750×H1900	선반(개)	3
내부크기(mm)	W750×D600×H1441	중량(kg)	110
내용적(L)	냉장전용 : 710	소비전력	380 W
온도범위	냉장 -10℃ ~ 10℃		



CWSR-850(1G)			
외부크기(mm)	W850×D750×H1900	선반(개)	2
내부크기(mm)	W750×D600×H1441	중량(kg)	115
내용적(L)	냉장전용 : 650	소비전력	380 W
온도범위	냉장 -10℃ ~ 10℃		



CWSR-830(2G)			
외부크기(mm)	W850×D750×H1900	선반(개)	3
내부크기(mm)	W750×D600×H1441	중량(kg)	105
내용적(L)	냉장전용 : 710	소비전력	380 W
온도범위	냉장 -10℃ ~ 10℃		



CWSR-1244(2G)			
외부크기(mm)	W1260×D800×H1900	선반(개)	6
내부크기(mm)	W1160×D650×H1441	중량(kg)	175
내용적(L)	냉장전용 : 1170	소비전력	450 W
온도범위	냉장 -10℃ ~ 10℃		



CWSR-1244(4G)			
외부크기(mm)	W1260×D800×H1900	선반(개)	6
내부크기(mm)	W1160×D650×H1441	중량(kg)	165
내용적(L)	냉장전용 : 1170	소비전력	450 W
온도범위	냉장 -10℃ ~ 10℃		

* 전원 : AC 220 V, 60 Hz

직냉식 25,30,45 올스텐 정육숙성고 (디지털)

Direct Cooling Meat Maturing Cabinets (Digital)



직냉식



디지털



24 hour
신선냉장



올스텐



냉기순환팬

| 재질 | 올스텐 | 컨트롤러 | 디지털

*정육숙성고 GRAND제품 별매



CWSRM-630(2G)			
외부크기(mm)	W627×D800×H1900	선반(개)	3
내부크기(mm)	W527×D650×H1441	중량(kg)	95
내용적(L)	냉장전용 : 530	소비전력	270 W
온도범위	냉장 -10℃ ~ 10℃		

*장도어 가능



CWSRM-830(1G)			
외부크기(mm)	W850×D750×H1900	선반(개)	3
내부크기(mm)	W750×D600×H1441	중량(kg)	110
내용적(L)	냉장전용 : 710	소비전력	380 W
온도범위	냉장 -10℃ ~ 10℃		



CWSRM-850(1G)			
외부크기(mm)	W850×D750×H1900	선반(개)	2
내부크기(mm)	W750×D600×H1441	중량(kg)	115
내용적(L)	냉장전용 : 650	소비전력	380 W
온도범위	냉장 -10℃ ~ 10℃		



CWSRM-830(2G)			
외부크기(mm)	W850×D750×H1900	선반(개)	3
내부크기(mm)	W750×D600×H1441	중량(kg)	105
내용적(L)	냉장전용 : 710	소비전력	380 W
온도범위	냉장 -10℃ ~ 10℃		



CWSRM-1244(2G)			
외부크기(mm)	W1260×D800×H1900	선반(개)	6
내부크기(mm)	W1160×D650×H1441	중량(kg)	175
내용적(L)	냉장전용 : 1170	소비전력	450 W
온도범위	냉장 -10℃ ~ 10℃		



CWSRM-1244(4G)			
외부크기(mm)	W1260×D800×H1900	선반(개)	6
내부크기(mm)	W1160×D650×H1441	중량(kg)	165
내용적(L)	냉장전용 : 1170	소비전력	450 W
온도범위	냉장 -10℃ ~ 10℃		

* 전원 : AC 220 V, 60 Hz



직냉식 25,30,45 올스텐 정육숙성고 유리문 (아날로그)

Direct Cooling Meat Maturing Cabinets (Analog)



직냉식



아날로그



24 hour



올스텐



냉기순환팬

| 재질 | 올스텐 | 컨트롤러 | 아날로그

*정육숙성고 GRAND제품 별매



CWSR-630(2G)			
외부크기(mm)	W627×D800×H1900	선반(개)	3
내부크기(mm)	W527×D650×H1441	중량(kg)	95
내용적(L)	냉장전용 : 530	소비전력	270 W
온도범위	냉장 -10℃ ~ 10℃		

*장도어 가능



CWSR-830(1G)			
외부크기(mm)	W850×D750×H1900	선반(개)	3
내부크기(mm)	W750×D600×H1441	중량(kg)	110
내용적(L)	냉장전용 : 710	소비전력	380 W
온도범위	냉장 -10℃ ~ 10℃		



CWSR-850(1G)			
외부크기(mm)	W850×D750×H1900	선반(개)	2
내부크기(mm)	W750×D600×H1441	중량(kg)	115
내용적(L)	냉장전용 : 650	소비전력	380 W
온도범위	냉장 -10℃ ~ 10℃		



CWSR-830(2G)			
외부크기(mm)	W850×D750×H1900	선반(개)	3
내부크기(mm)	W750×D600×H1441	중량(kg)	105
내용적(L)	냉장전용 : 710	소비전력	380 W
온도범위	냉장 -10℃ ~ 10℃		



CWSR-1244(2G)			
외부크기(mm)	W1260×D800×H1900	선반(개)	6
내부크기(mm)	W1160×D650×H1441	중량(kg)	175
내용적(L)	냉장전용 : 1170	소비전력	450 W
온도범위	냉장 -10℃ ~ 10℃		



CWSR-1244(4G)			
외부크기(mm)	W1260×D800×H1900	선반(개)	6
내부크기(mm)	W1160×D650×H1441	중량(kg)	165
내용적(L)	냉장전용 : 1170	소비전력	450 W
온도범위	냉장 -10℃ ~ 10℃		

* 전원 : AC 220 V, 60 Hz

직냉식 25,30,45 올스텐 정육숙성고 유리문 (디지털)

Direct Cooling Meat Maturing Cabinets (Digital)



직냉식



디지털



24 hour
신선냉장



올스텐



냉기순환팬

| 재질 | 올스텐 | 컨트롤러 | 디지털

*정육숙성고 GRAND제품 별매



CWSRM-630(2G)			
외부크기(mm)	W627×D800×H1900	선반(개)	3
내부크기(mm)	W527×D650×H1441	중량(kg)	95
내용적(L)	냉장전용 : 530	소비전력	270 W
온도범위	냉장 -10℃ ~ 10℃		

*장도어 가능



CWSRM-830(1G)			
외부크기(mm)	W850×D750×H1900	선반(개)	3
내부크기(mm)	W750×D600×H1441	중량(kg)	110
내용적(L)	냉장전용 : 710	소비전력	380 W
온도범위	냉장 -10℃ ~ 10℃		



CWSRM-850(1G)			
외부크기(mm)	W850×D750×H1900	선반(개)	2
내부크기(mm)	W750×D600×H1441	중량(kg)	115
내용적(L)	냉장전용 : 650	소비전력	380 W
온도범위	냉장 -10℃ ~ 10℃		



CWSRM-830(2G)			
외부크기(mm)	W850×D750×H1900	선반(개)	3
내부크기(mm)	W750×D600×H1441	중량(kg)	105
내용적(L)	냉장전용 : 710	소비전력	380 W
온도범위	냉장 -10℃ ~ 10℃		



CWSRM-1244(2G)			
외부크기(mm)	W1260×D800×H1900	선반(개)	6
내부크기(mm)	W1160×D650×H1441	중량(kg)	175
내용적(L)	냉장전용 : 1170	소비전력	450 W
온도범위	냉장 -10℃ ~ 10℃		



CWSRM-1244(4G)			
외부크기(mm)	W1260×D800×H1900	선반(개)	6
내부크기(mm)	W1160×D650×H1441	중량(kg)	165
내용적(L)	냉장전용 : 1170	소비전력	450 W
온도범위	냉장 -10℃ ~ 10℃		

* 전원 : AC 220 V, 60 Hz